



## General Purpose Corded Handheld Laser Bar Code Reader

With rich feature sets and extensive model options, the Gryphon™ product series from Datalogic Scanning represents the premium level of data collection equipment for general purpose applications.

For customers who want the high performance associated with laser scanning technology, the Gryphon GD4300 scanner is an ideal solution providing longer reading distances, snappy performance with a bright, well-defined scan line. Poor quality bar codes and low contrast labels with bad edge definition are not a problem for this Gryphon scanner, plus Datalogic's patented Green Spot provides visual good-read feedback directly on the code, allowing for fast and accurate scanning which is especially useful in noisy environments or in places where "beep-free" reading is desired. The scanner's stylish enclosure, light weight and compact size make it perfect for use in retail and office applications. Light industrial users will appreciate the scanners toughness. Its rubber-like overmold cushions the scanner when dropped,

protects the scan window and prevents the scanner from slipping off counter surfaces. Featuring an IP52 sealing rating, its strong enclosure guards against dust and liquid spills, and anti-shock mounts provide additional protection for the internal scan engine and optics.

The Gryphon GD4300 readers offer a choice of two sets of multi-interface options: USB, Keyboard Wedge, RS-232 and Wand Emulation, or for use at the point-of-sale (POS), IBM 46XX, USB and RS-232. Both interface sets offer configuration flexibility and are easily adapted for migration or future changes to the host system. Remote Host Download lowers the service costs and improves operations allowing for hassle-free field upgrades while the Datalogic Aladdin™ configuration software provides user-friendly features that simplify the start-up procedure, especially for inexperienced users.



## Features

- Aggressive reading performance: over 100 scans/second
- Excellent depth-of-field over 47.0 cm / 19.0 in
- Datalogic Green Spot for good-read feedback
- Remote Host Download lowers service costs and improves operations (GD4310 Model)
- Multi-interface solutions support most popular interfaces including USB, RS-232, Keyboard Wedge, IBM 46XX and Wand Emulation
- 1.8 m / 5.9 ft Drop Resistance
- Water and Particulate Sealing Rating: IP52
- USB Certified Kits Available



## Specifications

### DECODING CAPABILITY

1D / LINEAR CODES

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes

POSTAL CODES  
STACKED CODES

China Post  
GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional

### ELECTRICAL

CURRENT

Operating (Typical): GD4310: 185 mA @ 5 VDC;  
GD4330: 260 mA @ 5 VDC +/- 5%  
Standby/Idle (Typical): 30 mA @ 5 VDC  
GD4310: 4.5 - 14.0 VDC; GD4330: 4.75 - 5.25 VDC

INPUT VOLTAGE

### ENVIRONMENTAL

AMBIENT LIGHT  
DROP RESISTANCE

0 - 100,000 lux  
Withstands repeated drops from 1.8 m / 5.9 ft onto a concrete surface

ESD PROTECTION (AIR DISCHARGE)  
HUMIDITY (NON-CONDENSING)  
PARTICULATE AND WATER SEALING  
TEMPERATURE

16 kV  
5 - 90%  
IP52  
Operating: 0 to 55 °C / 32 to 131 °F  
Storage/Transport: 20 to 70 °C / -4 to 158 °F

### INTERFACES

RS-232 / IBM 46XX / USB Multi-Interface;  
RS-232 / USB / Keyboard Wedge / Wand Multi-Interface

### PHYSICAL CHARACTERISTICS

COLORS AVAILABLE  
DIMENSIONS  
WEIGHT

Black; White  
18.1 x 7.1 x 10.0 cm / 7.1 x 2.8 x 3.9 in  
169.0 g / 6.0 oz

### READING PERFORMANCE

LIGHT SOURCE  
PRINT CONTRAST RATIO (MINIMUM)  
READ RATE (MAXIMUM)  
READING ANGLE  
READING INDICATORS  
RESOLUTION (MAXIMUM)

Illumination: 630 - 680 nm VLD  
25%  
100 reads/sec.  
Pitch: +/- 50°; Roll (Tilt): +/- 35°; Skew (Yaw): +/- 65°  
Beeper (Adjustable Tone and Volume); Datalogic 'Green Spot' Good Read Feedback; Good Read LED  
0.102 mm / 4 mils

### READING RANGES

TYPICAL DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle.  
Printing resolution, contrast, and ambient light dependent.  
5 mils: 3.6 to 15.8 cm / 1.4 to 6.2 in  
7.5 mils: 3.0 to 25.0 cm / 1.2 to 9.9 in  
10 mils: 2.8 to 35.0 cm / 1.1 to 13.8 in  
13 mils: 2.2 to 47.5 cm / 0.9 to 18.8 in  
20 mils: Up to 69.0 cm / 27.2 in

### SAFETY & REGULATORY

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.

ENVIRONMENTAL COMPLIANCE  
LASER CLASSIFICATION

The Quick Reference Guide for this product can be referred to for a complete list of certifications.  
Complies to China RoHS; Complies to EU RoHS  
Caution Laser Radiation - Do not stare into beam; CDRH Class II;  
IEC 60825-1 Class 2

### UTILITIES

DATALOGIC ALADDIN™

Datalogic Aladdin configuration program is available for download at no charge

OPOS / JAVAPOS  
REMOTE HOST DOWNLOAD

OPOS Utilities are available for download at no charge  
Lowers service costs and improves operations

### WARRANTY

5-Year Factory Warranty

## Accessories

Mounts/Stands

- HLD-G040-BK: Desk/Wall Holder, G040, Black
- HLD-G040-WH: Desk/Wall Holder, G040, White
- STD-G040-BK: Basic Stand, G040, Dark
- STD-G040-WH: Basic Stand, G040, White



The USB-IF Logos are trademarks of Universal Serial Bus Implementers Forum, Inc.

© 2009 Datalogic Scanning, Inc.

All rights reserved. • Protected to the fullest extent under U.S. and international laws.  
• Copying or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries including the U.S.A. and the E.U. • Datalogic Aladdin is a trademark of Datalogic Scanning Group S.r.l. • Gryphon is a trademark of Datalogic Scanning, Inc. • Other brands and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-GRYPHONLGD4300-ENA4 20091211

[www.scanning.datalogic.com](http://www.scanning.datalogic.com)